

JCW-F16 Wire Stripping Twisting & Ferrule Crimping Machine



Features

1 vibrator bowl for all ferrules ranging from 0.3 to 16 sqmm

Stripping length up to 30mm

Crimping length up to 20mm

Servo motor control

User-friendly, robust and compact design

Technical Data

Model	JCW-F16 Servo Model Automatic Bootlace Ferrule and Wire Crimping Machine
Function	Single wire, Multicore cable, Wire end stripping, Conductor twisting, Tubular insulated terminal crimping, Quadrangle crimping, Stripping length, Cutting depth, Data library
Conductor cross-section	0.3, 0.5, 0.75, 1.0, 1.5, 2.5, 4.0, 6.0, 10, 16 mm ² [adjusting vibrator bowl]
Stripping length	6-30 mm
Crimping profile	Quadrilateral [imitating square]
Crimping length	Max 20 mm
Cycle time	3.2 seconds
Display	7" color touchscreen, English / Chinese [other languages on request]
Customize logo	Yes
Air supply	0.6 - 0.8 MPa (clean and dry air)
Rated power	1500 W
Power supply	AC 220V ± 10%, 10A, 50 / 60 Hz
Dimensions	L 365 x W 522 x H 430 mm
Weight	65 KG
CE-Conformity	Complies with CE equipment guidelines relative to mechanical and electrical safety and electromagnetic compatibility.